


PROTECTIVE CLOTHING CATEGORY III



INSTRUCTIONS FOR USE (PRODUCT CODE: HUAXIN-T)

Marking:

Each clothing is identified with an inside label, this indicates the type of protection offered and other points of information.

1. Manufacture's name.
2. CE marking – clothing complies with requirements for category III personal protective equipment according to REGULATION (EU) 2016/425. The testing of the prototype and subsequent CE registration was made at Shirley® Certification Services (Notify Body Number 2895).
3. Full-body protection "Types" achieved by Xianning Huaxin Garment Co., Ltd. defined by the European standards for Chemical Protective Clothing: Type 4 EN14605:2005+A1:2009, Type 5:EN 13982-1:2004, Type 6:EN 13034:2005. Clothing are tested against biological (EN14126) and radioactive (EN1073-2) hazards, antistatic EN1149-5 with

EN1149-1 and must be used with compatible accessories and work particles to be effective.

4. This garment is limited use protective clothing manufactured to meet standard EN ISO 13688:2013 protective clothing general requirements. Overall size.

Size	Chest (cm)	Height (cm)
S	84-92	164-170
M	92-100	170-176
L	100-108	176-182
XL	108-116	182-188
XXL	116-124	188-194

5. Wearer should read these instructions for use.
6. Year of manufacturing.
7. International care symbols: Do not wash, iron, machine dry, dry clean or bleach. Keep away from flames and heat.
8. Suitable for single use only-do not re-use.

PERFORMANCE CHART

Fabric Physical Properties		Class
Abrasion Resistance	EN 530 Meth.2	Class 1
Flex Cracking Resistance	ISO 7854 B	Class 4
Trapezoidal Tear Resist. MD	ISO 9073-4	Class 2
XD		Class 2
Puncture resistance	EN863	Class 1
Tensile Strength MD	ISO 13934-1	Class 1
XD		Class 1
Radioactive Protection	EN1073-2:2002	Class 2
Infective Resistance (solid particles)	ISO 22612	Class 3
Resistance to ignition	EN 13274-4	Pass
Fabric Chemical Properties	Penetration	Repellency
Test Method		
Resistance to chemical		
EN ISO6530	Classe 3	Classe 3
Sulphuric acid 30%	Classe 3	Classe 3
Sodium Hydroxide 10%	Classe 3	Classe 3
o-Xylene	Classe 3	Classe 3
Butance-1-ol	Classe 3	Classe 3

Whole suit test performance

Type 4 Spray Tight Method as EN14605:2005+A1:2009	Pass
Type 5 Inward leakage Method as defined by EN 13982-1&2:2004	Pass
Type 6 Light spray Method as defined by EN13134:2005	Pass
En14126:2003	Pass
Barrier to infective agents EN1073-2:2002	Pass
Barrier to radioactive particulates EN1149-5/18 Anti-static	Pass

Protection against Infective Agents EN14126

ISO 16603	Class 6
ISO 16604	Class 6
EN ISO 22610	Class 6
ISO 22611	Class 3
ISO 22612	Class 3

Areas of use:

Clothing designed for protection against hazardous substances and contamination of both product and personnel. They are typically used for protection against dry particles and low hazardous splashes and sprays. The determination for suitability of clothing is the final responsibility of the user. The suit may be contaminated on removal, and should be removed so as to avoid contamination of the user.

Limitations:

When using the clothing with other PPE and in order to comply fully with EN requirement for Type4/5/6 garment all openings such as wrist, ankles, neck etc., should be securely taped. The user shall be the sole judge of the suitability for the type of protection required and the correct combinations of clothing accessories and ancillary equipment. Upon contamination, wear or damage, the clothing should be removed and appropriately disposed of at the earliest opportunity. The wearer should always ensure to check the integrity of the clothing before wearing it. The possibility of heat stress should be considered in very warm conditions. Heat stress can be reduced or eliminated by the appropriate use of undergarments and ventilation equipment. Extreme of heat and cold may adversely affect the performance of this garment. The clothing should not be used where there is a risk to certain hazardous chemicals that have not been tested against. Although limited protection can be offered from various chemicals, please refer to the physical performance of the clothing in relation to Type4, Type 5 and 6 testing. The user must also wear compatible chemical resistant gloves, boots and respiratory protection. The gloves should cover the elastic cuffs. An appropriate size should be selected by the user to allow for unrestricted movement for the intended risk. If necessary please contact Manufacturer/Distributor for advice.

Storage and Disposal:

The clothing can be stored in accordance with normal storage practices, but we recommend storage in a dry place away from sources of light, heat and direct sunlight. Restrictions on the disposal depend solely on the contamination during use. The manufacturer cannot accept responsibility for any improper use or disposal of garments.

Expiration:

It is recommended that the product be used within a period of 3 years from the date of manufacture/production written on the packaging.

Approvals:

CE Approvals by:
(Notified Body: 2895)
Shirley® Port Tunnel Business Park,
Office 13 Unit 21, Dublin 17, ROI Ireland

REF	Product code
LOT	Lot number
Manufacturer	
Consult instructions for use	
Date of manufacture	
Expiration date	
CE	Requirements for category III personal protective equipment according to REGULATION (EU) 2016/425

REF

HUAXIN-T(S) (GIMA 21080)	TAPED SEAM INSULATION COVERALL - S - disposable
HUAXIN-T(M) (GIMA 21081)	TAPED SEAM INSULATION COVERALL - M - disposable
HUAXIN-T(L) (GIMA 21082)	TAPED SEAM INSULATION COVERALL - L - disposable
HUAXIN-T(XL) (GIMA 21083)	TAPED SEAM INSULATION COVERALL - XL - disposable
HUAXIN-T(XXL) (GIMA 21084)	TAPED SEAM INSULATION COVERALL XXL - disposable

Xianning Huaxin Garment Co., Ltd.
NO. 86, Guanbu Section, 107 National Highway
Xianning city, Hubei Province, China
Made in China

Imported by:
Gima S.p.A.
Via Marconi, 1 - 20060 Gessate (MI) Italy
gima@gimaitaly.com
export@gimaitaly.com
www.gimaitaly.com