


TAPED SEAM BOOT COVERS
Type PB4B-PB6B



INSTRUCTIONS FOR USE
(PRODUCT CODE: TBT)

Marking:

Accessories consisting of :
THD Hood; TBT Boots; TG Gown; TSC Shoe Covers;
TLB Lab Coat; TSL Sleeves; TAP Apron.

Accessories is identified with an inside label, this indicates the type of protection offered and other points of information.

1. Manufacture's name.
2. CE marking – Accessories complies with requirements for category III personal protective equipment according to REGULATION (EU) 2016/425. The testing of the prototype and subsequent CE registration was made at Shirley® Certification Ser-

3. Accessories protection "Types" achieved by Xianning Huaxin Garment Co., Ltd. defined by the European standards for Chemical Protective Clothing: Type PB 4B EN14605:2005+A1:2009, Type PB 6B: EN 13034:2005. Accessories are tested against biological (EN14126), antistatic EN1149-5 with EN1149-1 and must be used with compatible accessories and work particles to be effective.
4. Size: each accessory has one size.
5. Wearer should read these instructions for use.
6. Year of manufacturing.
7. International care symbols: Do not wash, iron, machine dry, dry clean or bleach. Keep away from flames and heat.
8. Suitable for single use only-do not re-use.

PERFORMANCE CHART

Fabric Physical Properties		Class
Abrasion Resistance	EN 530 Meth.2	Class 1
Flex Cracking Resistance	ISO 7854 B	Class 4
Trapezoidal Tear Resist. MD	ISO 9073-4	Class 2
	XD	Class 2
Puncture resistance	EN863	Class 1
Tensile Strength MD	ISO 13934-1	Class 1
	XD	Class 1
Infective Resistance (solid particles)	ISO 22612	Class 3
Resistance to ignition	EN 13274-4	Pass
Fabric Chemical Properties		Repellency
Test Method		
Resistance to chemical	EN ISO 6530	
Sulphuric acid 30%	Class 3	Class 3
Sodium Hydroxide 10%	Class 3	Class 3
o-Xylene	Class 3	Class 3
Butance-1-ol	Class 3	Class 3
Whole suit test performance		
Type 4 Spray Tight Method as EN14605:2005+A1:2009	Pass	
Type 6 Light spray Method as defined by EN13134:2005	Pass	
En14126:2003 Barrier to infective agents EN1149-5:2018 Anti-static	Pass	
Protection against Infective Agents EN14126		
ISO 16603	Class 6	
ISO 16604	Class 6	
EN ISO 22610	Class 6	
ISO 22611	Class 3	
ISO 22612	Class 3	

Areas of use:

Accessories designed for protection against hazardous substances and contamination of both product and personnel. They are typically used for protection against dry particles and low hazardous splashes and sprays. The determination for suitability of accessories is the final responsibility of the user. The suit may be contaminated on removal, and should be removed so as to avoid contamination of the user.

Limitations:

When using the accessories with other PPE and in order to comply fully with EN requirement for accessories all openings such as wrist, ankles, neck etc., should be securely taped. The user shall be the sole judge of the suitability for the type of protection required and the correct combinations of accessories and ancillary equipment. Upon contamination, wear or damage, the accessories should be removed and appropriately disposed of at the earliest opportunity. The wearer should always ensure to check the integrity of the accessories before wearing it. The possibility of heat stress should be considered in very warm conditions. Heat stress can be reduced or eliminated by the appropriate use of undergarments and ventilation equipment. Extreme of heat and cold may adversely affect the performance of this accessories. The accessories should not be used where there is a risk to certain hazardous chemicals that have not been tested against. Although limited protection can be offered from various chemicals, please refer to the physical performance of the accessories in relation to Type4, Type 5 and 6 testing. The user must also wear compatible chemical resistant gloves, boots and respiratory protection. The gloves should cover the elastic cuffs. An appropriate size should be selected by the user to allow for unrestricted movement for the intended risk. If necessary, please contact Manufacturer/Distributor for advice.

Storage and Disposal:

The accessories can be stored in accordance with normal storage practices, but we recommend storage in a dry place away from sources of light, heat and direct sunlight. Restrictions on the disposal depend solely on the contamination during use. The manufacturer cannot accept responsibility for any improper use or disposal of accessories.

Expiration:

It is recommended that the product be used within a period of 3 years from the date of manufacture/production written on the packaging.

Approvals:

CE Approvals by:
Shirley® Technologies (Europe) Limited
(Notify Body: 2895)
Port Tunnel Business Park, Office 13 Unit 21,
Dublin 17, ROI Ireland

	Product code
	Lot number
	Manufacturer
	Consult instructions for use
	Date of manufacture
	Expiration date
	Requirements for category III personal protective equipment according to REGULATION (EU) 2016/425

REF

TBT (21092) TAPED SEAM BOOT COVERS
Type PB4B-PB6B

Xianning Huaxin Garment Co., Ltd.
NO. 86, Guanbu Section, 107 National Highway
Xianning city, Hubei Province, China
Made in China

Imported by:
Gima S.p.A.
Via Marconi, 1 - 20060 Gessate (MI) Italy
gima@gimaitaly.com
export@gimaitaly.com
www.gimaitaly.com

