



Product Code	30625
Unit of sale	1 pc
Minimum order	1
Type	Medical device
Class	II B

UK-REP	Yes
CH-REP	No
RDM (NSIS)	514068
CND	Z12010902
EAN/UPC	8023279306255
GMDN	44776

## Description

DIATERMO 50 - monopolar

Radiofrequency electrocautery unit suitable for minor monopolar surgery.

Diatermo 50 through the function selection makes pure cut, cut coagulation (CUT 1 - CUT 2) and pure coagulation possible.

The one-board microcontroller and digital display guarantee high safety and reliability under any conditions.

They offer outstanding professional surgical results due to their ergonomic and superior safety features.

Made in Italy.

## Technical Specifications

- Max output power CUT: 50 W - 400 Ohm
- Max output power CUT/COAG1: 45 W - 400 Ohm
- Max output power CUT COAG2: 40 W - 400 Ohm
- Max output power COAG: 40 W - 400 Ohm
- Working frequency: 600 KHz
- Patient circuit: F
- Selectable input voltage: 115 - 230 Vac
- Mains frequency: 50 - 60 Hz
- Electrical input power: 200 VA
- Size W x H x D mm: 190 x 85 x 239
- Weight: 2.5 kg
- Controls: Patient/Plate circuit monitoring, Output power monitoring, Self check control
- Safety: EN60601-1, EN60601-1-2, EN60601-2-2
- Electrical Class: I CF
- MDD 93/42/EC Class: II b

## Standard accessories

- Single use handle
- Waterproof foot-switch (30577)
- MB flat neutral plate with cable (30564)
- Kit of 6 short autoclavable electrodes, Ø 2.4 mm, length 5 cm (30501/2/4/7/9/10)
- Power cable 2 m - Schuko plug
- User manual: GB, IT, available on request FR, ES