



Product Code	33220
Unit of sale	1 pc
Minimum order	1
Type	Medical device
Class	II A

RDM (NSIS)	1831648
CND	Z12050301
EAN/UPC	6945040100072
UMDNS	11407
PARAF	909435442

Description

- Large LCD display waveform and data
- High-resolution thermal printing array system
- Frequency response is as high as 150 Hz
- Capable of printing continuously on channel trace and annotations including lead mark and parameter such as sensitivity, paper speed and filter operation status
- High resolution digital filter inhibits baseline drift without affecting ECG waveform
- Floating input circuit meets IEC safety standard
- Rechargeable battery supporting more than 50 patient examinations
- Internal software: GB, IT, FR, ES, DE, TR.
- Manual: GB, IT, ES.

Technical Specifications

ECG instrument Input

- Safety Type: Class I, type CF applied part, which has defibrillation-proof applied part
- Lead Standard 12 leads
- Input way: Floating and defibrillation protection
- Patient leak current: $<10\mu\text{A}$
- Sampling rate: 800Hz
- A/D conversion: 12bit
- Frequency response 0.05Hz~150Hz (-3dB, + 0.4dB)
- Time constant: $>3.2\text{s}$
- CMRR: $>60\text{dB}$, $>100\text{dB}$ (Add filter)
- Enduring polarization voltage: $\pm 500\text{mV}$
- Noise level: $<15\mu\text{Vp-p}$

Dispose Wave Data

- EMG interference filter 35Hz (-3dB)
- AC filter 50Hz/60Hz ($\approx 20\text{dB}$)

Waveform output

- Recording way: Thermal printing system
- Recording paper: 50mm(W) \times 20m(L)
- Sensitivity: 5, 10, 20mm/mV
- Paper speed:
 - Auto-record: auto leads changing
 - Rhythm record: 25 mm/s, 50 mm/s
 - Manual-record: 25 mm/s, 50 mm/s

Power supply

- AC: 110-220V, 50/60 Hz
- DC: Lithium battery 7.4V, 2000 mAh

Fuse

- 2 pcs Ø5×20mm AC time lag; T250mA/250V(Power Supply:220V)

Form

- Size: 315 x 215 x 77 mm
- Net Weight: 1.5 kg

Standard accessories

- ECG cable - 1 set
- Limb electrode clamp - 1 set
- chest electrodes - 1 set
- Ground wire
- Power connection
- Paper roll