



Product Code	35124
Unit of sale	1 pc
Minimum order	1
Type	Medical device
Class	II B

CH-REP	Yes
RDM (NSIS)	1710880
CND	Z1203020201
EAN/UPC	8023279351248
PARAF	977815479

Description

"Vital Signs" is a line of small multi-parameter patient monitors, which can monitor the vital physiological parameters: non-invasive blood pressure (NIBP), pulse oxygen saturation (SpO2), electrocardiogram (ECG) and temperature (TEMP).

- Features:
- 3.5" LCD display for remote review
 - history data records reviewed in waveform, list and trend graph
 - USB connection for data output and software upgrade

Technical Specifications

- NIBP
- Measuring method: oscillometric
- Measurement mode: Manual, Auto, STAT
- Measurement range:
- Press SYS mmHg: (Adult 40-275) (Pediatric 40-200) (Neonate 40-135)
- Press MAP mmHg: (Adult 20-230) (Pediatric 20-165) (Neonate 20-110)
- Press DIA mmHg: (Adult 10-210) (Pediatric 10-150) (Neonate 10-95)
- SpO2
- SpO2 measurement range: 35% ~ 100%
- SpO2 measurement accuracy: 3% for range from 70 to 100%
- Low perfusion performance: as low as 0.4%
- Pulse rate
- Measurement range: 30 ~ 240 bpm
- Measurement accuracy: ± 2 bpm or ±2%, whichever is greater
- ECG
- Heart rate display range: 15 ~ 130 bpm
- Heart rate display accuracy: ± 1% or ±2 bpm, whichever is greater
- Heart rate alarm delay time: = 10s
- sensitivity selection: x1/4, x1/2, x1, x2
- Sweeping speed: 25 mm/s
- Temperature
- Measuring range: 21-50°C
- Measuring accuracy: ±0.2°C for range 25-45°C
- Other Technical Specifications
- Power supply: 100-240 VAC, 50/60 Hz
- Battery: 11.1 V, 4,400 mAh (Li-ion Battery)

Standard accessories

- Adult SpO2 probe
- NIBP adult cuff
- Temperature probe - skin type
- ECG cable + 10 ECG electrodes
- Lithium rechargeable battery
- Power supply cable
- Dust protective mantle
- Manual (GB, FR, IT, ES)