

iPAD CU-SP1 DEFIBRILLATOR - AED - GB,SE,FI,NO,DK,SK,CZ,HU,IL,KR specify language with order



Product Code	35355
Unit of sale	1 pc
Minimum order	1
Type	Medical device
Class	II B

RDM (NSIS)	1909642
CND	Z12030501
EAN/UPC	8023279353556
GMDN	47910

Description

IPAD CU-SP1 DEFIBRILLATOR - semi-automatic

Model: CU-SP1 - semiaut.

Joule: 150

Software voice: US, HU, CZ, NO, DK, SE, FI, SK, KR, IL

Online Manual*: US, CZ, NO, DK, SE, SK, KR, IL

*Languages listed in "Voice", but not in "Manual" have English manual.

Paper manual only for GB, IT

CU-SP1 is the latest generation of intelligent public access defibrillators with innovative features.

CU-SP1 Semi-Automated External Defibrillator (AED)

Easy-to-use, light and portable AED with battery. The AED automatically reads the patient's electrocardiogram (ECG) and determines if a cardiac arrest, that requires defibrillation, has occurred, so that both medical professionals and general public can easily operate it. Available 150 joule.

Features:

- Auto volume adjustment

It detects ambient noise and automatically adjusts volume of its prompts to make them audible over the background noise.

- Smart pads - intelligent storage

The pre-connected "Smart" electrode pads are stored in an easy access compartment on the underside of the unit. This ensures that the IPAD SP1 is always ready to be used in the shortest time possible. In addition, the visual frontal indicator shows if the connected pads are within their life expectancy. The indicator will change when the pads have only 3 months life left before their expiry date giving you time to arrange for replacements. It will change again when the expiry date is reached.

- CPR detection

CPR ensures that the casualty has the best chances of survival. The CU-SP1 detects if CPR is being performed with appropriate prompts, if not it encourages the responder to perform it.

- Easy communication with CU-EX1 software installation

CU-EX1 software on computer allows to see and analyze the usage history of the unit: time of "power on", the casualty's heart rhythm and shocks delivered are clearly presented.

Technical Specifications

Defibrillator

Operating mode: Semi-automatic

Waveform: e-cube biphasic (Truncated exponential type)

Energy: Adult: nominal 150J between 25 to 175 ohm/ Infant/child: nominal 50 joules at 50 ohm

Charge control: controlled by automated patient analysis system

Charging time: within 10 seconds since voice instruction "an electric shock is needed"
Sealing: waterjet proof IPX5 per IEC60529 (IP55); dust protected IP5X per IEC60529
Size - weight: 260x256x69.5 mm - 2.4 kg (including pads and battery)

User interface

User support: detailed voice prompts and flashing indicators
CPR guidance: voice prompts for how to perform CPR for adult and child
Controls: on/off button, "i" button, shock button
Indicator: LCD display (Device status, Battery status, Pads status)
Sensing: pads expiry date, Pads connection status
CPR Monitoring
Automatic Volume adjustment

Data recording and transmission

IrDA port / SD card: for PC communication
Internal Memory Data capacity: multi recording 5 individual events / Max 3 hours
Data review PC Programme: CU-EX1

Patient analysis system

Patient Analysis: Shockable Rhythms - Ventricular Fibrillation, Tachycardia
Sensitivity/Specificity Meets AAMI DF80 Guideline

Disposable high capacity battery

Standard Type: DC 12 Volt 4.2 Ah, Lithium manganese dioxide
Capacity: Minimum 200 shocks or 8 hours of operating time

Altitude operating range

Altitude 0-4,570 m (0-15,000 feet)

Standard accessories

Adult pads
Carrying bag
Disposable lithium battery pack
Paper manual (GB, IT)