



Product Code	80700
Unit of sale	1 pc
Minimum order	1
Type	No medical device
Class	

UK-REP	Not required
CH-REP	Not required
EAN/UPC	8023279807004

## Description

CMS 8000 VET PATIENT MONITOR ECG, RESP , SpO2, PR, NIBP, TEMP

- 12.1" TFT colour LCD display
- multilingual interface (GB, IT, FR, DE, ES, PT , NL, PL , CZ, TR , RO , RU)
- 8 channel waveform synchronous display
- 7 lead ECG waveform on one screen
- anti-motion, anti-ambient light interference digital SpO2 technology
- AC/DC rechargeable lithium battery
- manual/AUTO/continuous NIBP measurement mode
- standard/OXY- graph/Trend-graph/big characters and view bed interfaces

## Technical Specifications

### ECG

5-lead, dual channel, 3-lead, single channel  
 Scan speed: 12.5, 25, 50 mm/s  
 ST segment monitoring  
 Measurement and alarm range: -2.0 mV  $\pm$ 2.0 mV

### RESP

Method: R-F (RA-LL) impedance  
 Measurement and alarm range: 0-150 rpm  
 Apnea alarm: 10-40 sec

### NIBP - Oscillometric method

Mode: manual/AUTO/continuous  
 Measurement interval in AUTO mode:  
 1/2/3/4/5/10/15/30/60/90/120/240/480/960 min  
 Measurement period in CONT mode: 5 min  
 Measurement alarm: 10-270 mmHg

### SpO2

Measurement and alarm range: 0-100%  
 Measurement accuracy: 70-100%  $\pm$ 2%

### PR

Measurement and alarm range: 25-250 bpm

### TEMP

Measurement and alarm range: 0-50 °C

### DEVICE

Power supply: 100-240 V - 50/60 Hz

Safety classification: Classe I type CF  
Defibrillation-proof applied part

## Standard accessories

- Vet SpO2 probe - 3 m
- 5 leads ECG cable with metal clamps
- NIBP cuff 6-11 cm and extension tube
- Power supply cable
- Temperature probe - rectal
- Manual: GB, IT
- Rechargeable lithium battery